



**ESSENTIAL SERIES**  
GENERAL PURPOSE LED BULBS



**KT-LED6R20-9CSF /G4**  
GENERAL PURPOSE LED LAMP

**DESCRIPTION**

R20 Flood | E26 Medium Base | Color Select | Dimmable | 25,000hr Lifetime

**APPLICATIONS**

- Recessed lighting
- Track lighting
- Surface-mount ceiling fixtures



**RoHS**  
Compliant



**3 YEAR**  
WARRANTY

**PRODUCT FEATURES**

- 80%+ energy savings and less heat generation vs legacy equivalents
- 25,000 hr lifetime means fewer replacements and lower maintenance cost
- Smooth diffused lens for comfortable, glare free performance
- Durable plastic housing for lower risk of breakage
- ANSI compliant construction ensures fit for intended applications
- UL Certified
- Not suitable for use in totally enclosed fixtures
- Suitable for dry and damp locations
- Suitable for use with dimmers  
*(see compatibility list for comprehensive list of approved dimmers)*
- PF > 0.90
- Operating temperature range: 4°F/-20°C to 104°F/40°C
- Complies with FCC Part 15

**PERFORMANCE SPECIFICATIONS**

Catalog Number	Wattage	Selectable CCT	Lumens	Efficacy	Input Voltage	Dimming	CRI	Base Type	Beam Angle	Legacy Equivalent
KT-LED6R20-9CSF /G4	6W	2700K	550	92 lm/W	120V	Yes	>90	E26	110°	50W
		3000K								
		3500K								
		4000K								
		5000K								



**ESSENTIAL SERIES**  
GENERAL PURPOSE LED BULBS



# KT-LED6R20-9CSF /G4

## GENERAL PURPOSE LED LAMP

### PHYSICAL SPECIFICATIONS

Lamp Dimensions	
A (Diameter)	2.50"
B (Length)	3.82"

**BASE TYPE:** E26 (Medium)

Packaging	
Carton Quantity	24 pcs
Carton Dimensions	10.83" × 8.58" × 8.15"
Carton Weight	3.95 lbs

### ORDERING INFORMATION

Catalog Number	UPC	Easy Code
KT-LED6R20-9CSF /G4	843654175959	ATS-11

### CATALOG NUMBER BREAKDOWN

# KT-LED6R20-9CSF /G4

1 2 3 4 5 6 7 8

- 1 Keystone Technologies
  - 2 LED Lamp
  - 3 Wattage
  - 4 Lamp Shape
  - 5 90 CRI
  - 6 Color Select
  - 7 Color Select Designation
  - 8 Generation 4
- 8 Color Select Designation**
- |   |                           |
|---|---------------------------|
| F | 2700/3000/3500/4000/5000K |
|---|---------------------------|